PROJECT MOTES 1. A NOTICE OF NETTER THIS PROJECT, THE DISTURBED BEALTS 2.21 ALRESS FOR PROJECT INFORMS INSTALLATION OF STREAMS AND CORRESPONDED. 2. ALL BOTTOM FOR ACCOUNTING THAT ACT TO BE PROJECT TO THE PROJECT OF THE ACCOUNTING THAT ACT TO BE PROJECT TO THE PROJECT OF THE ACCOUNTING THAT ACT TO BE PROJECT OF THE ACCOUNTING THAT ACCOUNTING THAT ACCOUNTING THE ACCOUNTING THAT ACCOUNTING THE ACCOUNTING TO WASHING TO WASHING THE ACCOUNTING TO WASHING THE ACCOUNTING TO WASHING THE ACCOUNTING THE ACCOUNTING TO WASHING THE ACCOUNTING THE ACCOUN		1:04:26 PM GPLOT-V8	K:\AMT_Roadway\0 5663 60_SRTS TO 24 Ba dwin\CAD\00 0455_04-00 .dgn			STATE	PROJECT NUMBER	SHEE	ET NO. TOTA
1. A NOTICE OF INITITY IS REQUIRED FOR THIS PROJECT. THE DISTURBED AREA IS 2.21 AND STATEMENT OF THAT AND THE STREAMERS AND COORDER PARKS. 2. ALL DRIVEWAYS THAT AND TO BE RECONSTRUCTED SHALL BE PLACED IN KIND 1.1.E. ASPHALT FOR SCHALL, SHALL DRIVEWAY RELOCATIONS ARE SHOWN FROM THE BEST ANALABLE DOST FOR ADAPTA DISTORMENT OF THE ANALABLE SHALL BE SHOWN FROM THE BEST ANALABLE DATA. THE CONTRACTOR SHALL BE DISTOR CONSTRUCT BY DIFFERENCE IN THE PLACE OF THE ADAPTA DIVISION OF ELISTING DRIVEWAYS ON AS LOCATED IN THE PLACE OF THE ADAPTA DIVISION OF ELISTING DRIVEWAYS ON AS LOCATED IN THE PLACE OF THE ADAPTA DIVISION OF ELISTING DRIVEWAYS ON AS LOCATED IN THE PLACE OF THE ADAPTA DIVISION OF ELISTING DRIVEWAYS ON AS LOCATED IN THE PLACE OF THE ADAPTA DIVISION OF EXISTING STRIPING IS TO BE INCLUDED IN THE PRICE BID FOR THAT FOR CONTRACT. THE PRICE BID FOR CONTRACT OF THE ADAPTA DIVISION OF EXISTING STRIPING IS TO BE INCLUDED IN THE PRICE BID FOR THAT FOR CONTRACT. THE PRICE BID FOR THAT BOTH THE ACTION AND THE ADAPTA DIVISION OF EXISTING STRIPING IS TO BE INCLUDED IN THE PRICE BID FOR THAT FOR CONTRACT. AND THE PRICE BID FOR CONTRACT OF THE ADAPTA DIVISION OF THIS PROJECT AND EXISTING STRIPING IS TO BE INCLUDED IN THE PRICE BID FOR THAT FOR CONTRACT. ALL ADD ANALYS SHALL BE 28 FEET WILD AT THE PRICE BID FOR THAT BOTH ARE PRICE BID FOR THAT FOR CONTRACT. AND THE PRICE BID FOR CONTRACT OF THE BOTH ARE PRICE BID FOR THAT BOTH ARE PRICE BID FOR THAT BOTH ARE PRICE BID FOR THAT BOTH ARE PRICE BID FOR CANDING COUNTERS. ASPHALT - RESIDENTIAL - CONNECTE VALLEY GUTTER, 8' GRADED AGREENATE BASE, 6' CONCRETE - CONNECTE VALLEY GUTTER, 8' GRADED AGREEDATE BASE, 6' CONCRETE - CONNECTE VALLEY GUTTER, 8' GRADED AGREEDATE BASE, 6' ASPHALT - RESIDENTIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGREEDATE BASE, 6' ASPHALT - RESIDENTIAL - CONCRETE VALLEY GUTTER, 8' ASPHALT - RESIDENTIAL	ry.godwin	gplotborder-v8i-P0.tbl				GA	0010455		4
2. ALL DRIVEWAYS THAT ARE TO BE RECONSTRUCTED SHALL BE PLACED IN KIND LIFE. ASPHALT FOR ASPHALT, CONCRETE FOR CONCRETE, AND AGREGATE SUPERAGE OURSE FOR DIFFE DRIVEST. DIFFERENCE OF CONCRETE FOR CONCRE		PROJECT NOTES							
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		I. A NOTICE OF INTENT IS REQUIRED FOR THIS PROJECT. THE DISTURBED AREA IS 2.21 ACRES. THE PROJECT INVOLVES INSTALLATION OF SIDEWALKS AND CURB RAMPS, A MULTI-USE TRAIL, AND ONE PEDESTRIAN BRIDGE.	7. ALL ADA RAMPS AND SIDEWALK WITHIN THE INTERSECTION RADII ARE TO BE 8 INCH CONCRETE. THE COST FOR ADA RAMPS AND DETECTABLE WARNINGS SHALL BE INCLUDED IN THE PRICE BID FOR CONC SIDEWALK, 8 IN.						
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		2. ALL DRIVEWAYS THAT ARE TO BE RECONSTRUCTED SHALL BE PLACED IN KIND (I.E.	8. ALL DETECTABLE WARNING SURFACES ARE TO BE THE COLOR YELLOW.						
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		DIRT DRIVES). DRIVEWAY RELOCATIONS ARE SHOWN FROM THE BEST AVAILABLE DATA.			Pi			ES	
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		LOCATION OF EXISTING DRIVEWAYS OR AS LOCATED IN THE PLANS. RESIDENTIAL ORIVES SHALL REFET WIDE AT THE THROAT UNIESS NOTED OTHERWISE IN THE	IO. ALL REMOVAL OF EXISTING STRIPING IS TO BE INCLUDED IN THE PRICE BID FOR TRAFFIC CONTROL.		<u> </u>	TON TILDMONTIALO	TE KIDOL KEGION		
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		PLANS. COMMERCIAL DRIVES SHALL BE 24 FEET WIDE UNLESS NOTED OTHERWISE IN THE PLANS. THE CONTRACTOR SHALL ORTAIN THE APPROVAL FROM THE ENGINEER PRIOR			C	20000001750 0755			
CONCRETE - RESIDENTIAL - CONCRETE VALLEY GUTTER, 6' GRADED AGGREGATE BASE, 6' CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' ASPHALT - RESIDENTIAL - ASPH CONC 12. 5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' 12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE ASSHOOL AGGREGATE BASE, 8' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE GRADED AGGREGATE BASE, 6' 15. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED CORRUGATED STORY ALUMINUM ASHOO ASSHOOL ASHOOL ASHO		TO MAKING ANY REVISIONS TO LOCATION, WIDTH, AND/OR NUMBER OF DRIVES TO BE CONSTRUCTED. DRIVES SHALL BE CONSTRUCTED USING:	COORDINATE SYSTEM OF 1984 (NAD 1983)/94 WEST ZONE, AND THE NORTH AMERICAN VERTICAL DATUM (NAVD) OF 1988. ADDITIONAL PORTIONS OF THIS PROJECT HAVE BEEN		0 N		AASHTO	PLASTIC	
CONCRETE - COMMERCIAL - CONCRETE VALLEY GUTTER, 8' GRADED AGGREGATE BASE, 8' ASPHALT - RESIDENTIAL - ASPH CONC 12.5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6' FOR THIS PROJECT. 1. CONCRETE VALLEY GUTTER, 8' CONCRETE VALLEY GUTT					C R		CORRUGATE	CORR.POLY- POLY VINY	L POLY VINYL
ASPHALT - RESIDENTIAL - ASPH CONC 12.5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6" 13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE PRICE BID FOR GRADING COMPLETE. ASPHALT - RESIDENTIAL - ASPH CONC 12.5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6" 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE PRICE BID FOR TRAFFIC CONTROL TRAVEL BEARING COST FOR THAT WORK IS TO BE INCLUDED IN THE PRICE BID FOR TRAFFIC CONTROL			12. A SUBSURFACE UTILITY ENGINEERING (SUE) INVESTIGATION WAS NOT PERFORMED FOR THIS PROJECT.		E T	COATED PLAIN	PLAIN POLY- UNCOATED FTHYLENE	SMOOTHED CHLORIDE UNED PROFUE	CHLORIDE (PVC) CORRUGATED
ASPHALT - RESIDENTIAL - ASPH CONC 12.5mm SUPERPAVE (165 LB/SY) GRADED AGGREGATE BASE, 6" 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE INTERSTATE AND THE PRICE BLD FOR TRAFFIC CONTROL TRAVEL BEARING		CONCRETE - COMMERCIAL - CONCRETE VALLEY GUITER, 8" GRADED AGGREGATE BASE, 8"	13. ALL EXISTING TREE LIMBS IN CONFLICT TO BE TRIMMED TO A HEIGHT OF 7' AND THE		Ε		ALUMINUM AASHTO	AASHTO WALL M-294 AASHTO	SMOOTH INTERIOR
GRADED AGGREGATE BASE, 6' 14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE COST FOR THAT WORK IS TO BE INCLUDED IN THE PRICE BID FOR TRAFFIC CONTROL. 3. ALL BORROW AND WASTE SITES FOR THIS PROJECT SHALL BE ENVIRONMENTALLY APPROVED PRIOR TO CONSTRUCTION ACTIVITIES OCCURRING IN THEM. ALL COMMON FILL OR EXCESS MATERIAL DISPOSED OUTSIDE THE PROJECT RIGHT OF WAY SHALL BE PLACED IN EITHER A PERMITTED SOLID WASTE FACILITY, A PERMITTED INERT WASTE LANDFILL OR IN AN ENGINEERED FILL: SEE SECTION 201 OF THE STANDARD SPECIFICATION AND SUPPLEMENTS THERETO FOR		ASPHALT - RESIDENTIAL - ASPH_CONC_12.5mm SUPERPAVE (165 LB/SY)			\ \ /			TYPE "S" M-304	ASTM F-949
3. ALL BORROW AND WASTE SITES FOR THIS PROJECT SHALL BE ENVIRONMENTALLY APPROVED PRIOR TO CONSTRUCTION ACTIVITIES OCCURRING IN THEM. ALL COMMON FILL OR EXCESS MATERIAL DISPOSED OUTSIDE THE PROJECT RIGHT OF WAY SHALL BE PLACED IN EITHER A PERMITTED SOLID WASTE FACILITY, A PERMITTED INERT WASTE LANDFILL OR IN AN ENGINEERED FILL: SEE SECTION 201 OF THE STANDARD SPECIFICATION AND SUPPLEMENTS THERETO FOR			14. ALL EXISTING SIGNS THAT ARE IN CONFLICT ARE TO BE REMOVED AND RESET AND THE COST FOR THAT WORK IS TO BE INCLUDED IN THE PRICE BID FOR TRAFFIC CONTROL.		X				
MATERIAL DISPOSED OUTSIDE THE PROJECT RIGHT OF WAY SHALL BE PLACED IN EITHER A PERMITTED SOLID WASTE FACILITY, A PERMITTED INERT WASTE LANDFILL OR IN AN ENGINEERED FILL: SEE SECTION 201 OF THE STANDARD SPECIFICATION AND SUPPLEMENTS THERETO FOR WATERIAL DISPOSED OUTSIDE THE PROJECT RIGHT OF WAY SHALL BE PLACED IN EITHER A WON-TRAVEL BEARING			COST FOR THAT WORK IS TO BE INCLUDED IN THE PRICE BID FOR TRAFFIC CONTROL.	LONGITUDINAL	X	X	X	Y Y	<u> </u>
FILL: SEE SECTION 201 OF THE STANDARD SPECIFICATION AND SUPPLEMENTS THERETO FOR		MATERIAL DISPOSED OUTSIDE THE PROJECT RIGHT OF WAY SHALL BE PLACED IN EITHER A PERMITTED SOLID WASTE FACILITY A PERMITTED INFRT WASTE LANDELL OR IN AN ENGINEERED	UTILITY OWNERS	S	1 //	\		// //	
		FILL. : SEE SECTION 201 OF THE STANDARD SPECIFICATION AND SUPPLEMENTS THERETO FOR	FACILITY OWNER	' C ADT < 250	X	X	X	XX	X

FACILITY	OWNER
ELECTRIC	GEORGIA POWER (DISTRIBUTION)
ELECTRIC	BALDWIN COUNTY SCHOOLS
PHONE	PROGRESSIVE COMMUNICATIONS FKA ANS CONNECT
PHONE	WINDSTREAM
PHONE	BALDWIN COUNTY SCHOOLS
GAS	ATLANTA GAS LIGHT
CABLE	CHARTER COMMUNICATIONS
WATER	BALDWIN COUNTY SCHOOLS
WATER	MILLEDGEVILLE WATER AND SEWER
WATER	BALDWIN COUNTY WATER AND SEWER
SEWER	BALDWIN COUNTY SCHOOLS
SEWER	MILLEDGEVILLE WATER AND SEWER
SEWER	BALDWIN COUNTY WATER AND SEWER

ENVIRONMENTAL RESOURCES IMPACT TABLE									
Resource Name/Type	Location	Side	Construction Activity	Permitted Activity	Controlling Criteria	Special Provision?	Comments including any permit expiration dates		
Environmental Resource- Perennial Stream I	Blandy Rd. Sta. 108+70 to 109+45	Right	Sidewalk/bridge construction, erosion control	None	Section 404 of the Clean Water Act	N/A	See Note I below		
Environmental Resource- Perennial Stream I Buffer	Blandy Rd. Sta. 108+45 to 109+70	Right	Sidewalk/bridge construction, erosion control	None	Section 404 of the Clean Water Act	N/A	See Note I below		
Environmental Resource- Perennial Stream 2	S ABC St. Sta. 221+26 to 221+33 N ABC St. Sta. 507+85 to 508+39	Right	S ABC St. Sidewalk, erosion control N ABC St. No Activity	None	Section 404 of the Clean Water Act	N/A	See Note 2 below		
Environmental Resource- Perennial Stream 2 Buffer	S ABC St. Sta. 221+01 to 221+58 N ABC St. Sta. 507+60 to 508+64	Right	S ABC St. Sidewalk, erosion control N ABC St. No Activity	None	Section 404 of the Clean Water Act	N/A	See Note 2 below		
Birds	Blandy Road Sta. 108+25 to 110+00 S ABC St. Sta. 220+99 to 221+31 N ABC St. Sta. 507+88 to 508+21	N/A	Sidewalk/bridge construction, erosion control	None	MBTA	Yes SP107.23G	See Note 3 below		

4. THERE IS NO SUITABLE PLACE TO BURY EXISTING CONSTRUCTION DEBRIS WITHIN THE PROJECT'S LIMITS. THE CONTRACTOR SHALL PROVIDE AN ENVIRONMENTALLY APPROVED SITE TO DISPOSE OF EXISTING CONSTRUCTION DEBRIS AT NO ADDITIONAL COST TO THE DEPARTMENT.

5. REMOVAL OF EXISTING PAVEMENT, CURB AND GUTTER, AND CONCRETE SIDEWALK, INCLUDING SAWCUTTING, AS SHOWN IN PLANS, SHALL BE INCLUDED IN PRICE BID FOR GRADING COMPLETE.

6. AT ALL LOCATIONS WHERE EXISTING CURB OR PAVEMENT ABUTS NEW CONSTRUCTION, THE EDGE OF THE EXISTING CURB OR PAVEMENT SHALL BE SAWCUT TO A CLEAN, SMOOTH EDGE IN ACCORDANCE WITH SECTION 411 AND 444. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE PRICE BID FOR GRADING COMPLETE.

Note:
I. The contractor shall ensure that no land disturbing activities, including staging, construction, vehicular use, borrow or waste activities shall take place within the boundaries of PS-I or its associated buffer.

2. The contractor shall ensure that no land disturbing activities, including staging, construction, vehicular use, borrow or waste activities shall take place within the boundaries of PS-2 or its associated buffer.

3. Special Provision 107.23G will be implemented for the protection of birds.

				E	(TYPE 2) CORRUGATED STEEL	COATED	ALUMINUM	AASHTO M-252	LINED AASHTO M-294 TYPE "S"	PROFILE WALL AASHTO M-304	CORRUGATED SMOOTH INTERIOR ASTM F-949
	LONGITUDINAL INTERSTATE AND TRAVEL BEARING			X							
		LONGITUDINAL NON-INTERSTATE AND NON-TRAVEL BEARING		X	X		X		X	X	X
S T 0	C		ADT < 250	X	X		X		X	X	X
R	R 0 S	GRADE	250 < ADT < 1,500	X	X *		X		X	X	X
D R	S D	< 10%	1,500 < ADT < 15,000	X					X	X	X
$A \mid F$	R A		ADT > /5,000	X							
	N	GRADE > 10%	ADT < 250		X		X		X	X	X
			ADT > 250				X		X	X	X
	SIDE DRAIN PERMANENT SLOPE DRAIN			X	X		X		X	X	X
F					X	X	X		X	X	X

* This type pipe can be used if the addition of Type "B" Coating (AASHTO M-190, Half Bituminous Coated with Paved Invert) is utilized.

NOTES:

Rev. 03-22-10

PERFORATED UNDERDRAIN

- I. Allowable materials are indicated by an "X".
- 2. Structural requirements of storm drain pipe will be in accordance with Georgia Standard 1030-D or 1030-P, whichever is applicable, and the Standard Specifications.
- 3. Graded aggregate backfill shall be used in cross drain applications for all plastic pipes (AASHTO M-294, HDPE pipe; AASHTO M-304, PVC pipe; ASTM F-949, PVC pipe).
- 4. The Contractor shall provide additional storm sewer capacity calculations if a pipe
- material other than concrete is selected.
- 4. Pipe used under mechanically stabilized earth (MSE) walls, within MSE wall backfill, or within five feet of an MSE wall face shall be Class V Concrete Pipe.
- 4. Project specific pH and Resistivity values are entered into the respective boxes above to determine allowable pipe materials.



Know what's Delow. Call before you dig.

REVISION DATES	STATE OF GEORGIA DEPARTMENT OF TRANSPORTATION					
	OFFICE:	PROGRAM DELIVERY				
		GENERAL NOTES				
			<u> </u>			
			$ \begin{array}{c} \text{DRAWING No.} \\ \text{DA} = \text{DO} \\ \text{DA} \end{array} $			

Kimley-Horn and Associates, Inc. Engineering, Planning, and Environmental Consultants 817 W. Peachtree Street NW, Suite 601 Atlanta, GA 30308

12/14/2012